

---

Subject: How to Print Interlocking Parts? Also, which material?  
Posted by [vaguelygenius](#) on Fri, 01 Mar 2013 20:41:09 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hello! I've made a 3D model i want to print and it's my first time ever getting something printed. I tried uploading this model all together so the pointers will print attached to the main body, but Shapeways did not like it and rejected the design. However, it seemed fine when I tried uploading the part separately. What can I do to get this printed all together?

Also, I'm not entirely sure what material I should be picking. I'm mostly concerned with it withstanding some light banging since it is a prop, and to have a nice and smooth surface, since it's mostly curves. Any advice? I was looking at Polished WSF, hoping it won't round out the points too much...

---

#### File Attachments

1) [Completed Ring Image.png](#), downloaded 92 times

---

---

Subject: Re: How to Print Interlocking Parts? Also, which material?  
Posted by [Youknowwho4eva](#) on Fri, 01 Mar 2013 20:53:42 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Make sure your gaps are at least .5mm to prevent fusing. Polishing will dull your points but not a whole lot. I actually got some pointy parts the other day in polished dyed nylon, and they are still pretty sharp.

---

---

Subject: Re: How to Print Interlocking Parts? Also, which material?  
Posted by [vaguelygenius](#) on Fri, 01 Mar 2013 21:24:42 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Thanks for your quick reply, but I went back and made sure that there was .5mm clearance between the parts and the system still rejected it... ): I uploaded it as a .wrl file because exporting it as an STL file in Solidworks makes every component a separate file, preventing them from interlocking...

---